SAFETY DATA SHEET



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	· · · · · · · · · · · · · · · · · · ·
Trade name or designation	Hylomar M all grades (Light, Medium and Heavy)
of the mixture	rigional w all grades (Light, weddin and heavy)
Registration number	-
•	None.
Synonyms	
SDS number	1
Issue date	04-April-2016
Version number	01
Revision date	-
Supersedes date	-
1.2. Relevant identified uses of	the substance or mixture and uses advised against
Identified uses	Non-Setting and Non-Hardening Gasketing Compound.
Uses advised against	None known.
1.3. Details of the supplier of the	ne safety data sheet
Supplier:	WINKEL GmbH
Address:	Lisztstraße 1
	53881 Euskirchen - Germany
Talaahaa amadaa	+49 2251 77 69 400-401
Telephone number:	
Fax:	+49 2251 77 69 402
E-mail address:	info@winkelgroup.de
Web:	www.winkelgroup.de
1.4. Emergency telephone number	In case of a life-threatening emergency: 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards Flammable liquids		Category 2	H225 - Highly flammable liquid and vapour.
Health hazards Serious eye damage/eye irritation		Category 2	H319 - Causes serious eye irritation.
Specific target organ toxicity - single exposure		Category 3 narcotic effects	H336 - May cause drowsiness or dizziness.
Hazard summary	Highly flamma dizziness.	ble liquid and vapour. Causes serious e	ye irritation. May cause drowsiness or
2.2. Label elements Label according to Regulation (I	EC) No. 1272/20	08 as amended	

Contains: Acetone

Hazard pictograms



Signal word	Danger
Hazard statements	
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
Precautionary statements	
Prevention	
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
Response	
P312	Call a POISON CENTRE or doctor/physician if you feel unwell.
Storage	
P403 + P235	Store in a well-ventilated place. Keep cool.
P233	Keep container tightly closed.
Disposal	
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
Supplemental label information	EUH066 - Repeated exposure may cause skin dryness or cracking.
2.3. Other hazards	Not a PBT or vPvB substance or mixture.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
Acetone	25 - 50	67-64-1 200-662-2	-	606-001-00-8	#
Classification:	Flam. Liq. 2;H225, Eye I	rrit. 2;H319, STOT	SE 3;H336		

List of abbreviations and symbols that may be used above

#: This substance has workplace exposure limit(s).

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
4.1. Description of first aid meas	sures
Inhalation	Move into fresh air and keep at rest. If not breathing, give artificial respiration or give oxygen by trained personnel. Get medical attention if any discomfort continues.
Skin contact	Take off immediately all contaminated clothing. Wash skin thoroughly with soap and water. If irritation persists get medical attention.
Eye contact	Flush eyes thoroughly with water for at least 15 minutes. Remove any contact lenses. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly. Drink a few glasses of water or milk. Get medical attention if any discomfort continues.
4.2. Most important symptoms and effects, both acute and delayed	Irritation of eyes and mucous membranes. Exposed individuals may experience eye tearing, redness, and discomfort. Vapours may cause drowsiness and dizziness.
4.3. Indication of any immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically.

SECTION 5: Firefighting measures

General fire hazards

The product is highly flammable, and explosive vapour/air mixtures may be formed even at normal room temperatures. Vapours are heavier than air and may travel along the ground to some distant source of ignition and flash back.

5.1. Extinguishing media	
Suitable extinguishing media	Water spray, foam, dry powder or carbon dioxide.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
5.2. Special hazards arising from the substance or mixture	By heating and fire, harmful vapours/gases may be formed.
5.3. Advice for firefighters	
Special protective equipment for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace.
Special fire fighting procedures	Cool containers exposed to heat with water spray and remove container, if no risk is involved. Prevent runoff from fire control or dilution from entering streams, sewers or drinking water supply.

SECTION 6: Accidental release measures

6.1. Personal precautions, protection	ctive equipment and emergency procedures
For non-emergency personnel	Keep upwind. Ventilate closed spaces before entering them. Avoid inhalation of vapours/spray and contact with skin and eyes. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
For emergency responders	Keep unnecessary personnel away. Wear protective clothing as described in Section 8 of this safety data sheet.
6.2. Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not discharge into drains, water courses or onto the ground.
6.3. Methods and material for containment and cleaning up	Eliminate all ignition sources. Ventilate the area. Wipe up with absorbent material (e.g. cloth, fleece). Transfer to a container for disposal. Following product recovery, flush area with water.
6.4. Reference to other sections	For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling	Keep away from sources of ignition - No smoking. Use only outdoors or in a well-ventilated area. Avoid inhalation of vapours/spray and contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet. Avoid prolonged exposure. Wash thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices. Avoid release to the environment.
7.2. Conditions for safe storage, including any incompatibilities	Keep container tightly closed in a cool, well-ventilated place. Keep away from heat, spark, open flames and other sources of ignition. Store away from incompatible materials.
7.3. Specific end use(s)	Non-Setting and Non-Hardening Gasketing Compound.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

UK. EH40 Workplace Exposure Limits (WELs)

Components	Туре	Value	
Acetone (CAS 67-64-1)	STEL	3620 mg/m3	
		1500 ppm	
	TWA	1210 mg/m3	
		500 ppm	

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU

Components	Туре	Value	
Acetone (CAS 67-64-1)	TWA	1210 mg/m3	
		500 ppm	
Biological limit values	No biological exposure limits noted fo	r the ingredient(s).	
Recommended monitoring procedures	Follow standard monitoring procedure	S.	
Derived no-effect level (DNEL)	Not available.		
Predicted no effect concentrations (PNECs)	Not available.		

8.2. Exposure controls

Appropriate engineering controls	Provide adequate ventilation. Observe Occupational Exposure Limits and minimise the risk of inhalation of vapours. Use explosion-proof equipment.		
Individual protection measure	s, such as personal protective equipment		
General information	Personal protective equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.		
Eye/face protection	If eye contact is likely, safety glasses with side shields or chemical type goggles should be worn.		
Skin protection			
- Hand protection	Wear protective gloves. Butyl rubber gloves are recommended. Breakthrough time >120 min. Be aware that the liquid may penetrate the gloves. Frequent change is advisable. Suitable gloves can be recommended by the glove supplier.		
- Other	Normal work clothing (long sleeved shirts and long pants) is recommended.		
Respiratory protection	In case of inadequate ventilation or risk of inhalation of vapours, use suitable respiratory equipment with gas filter (type A2). If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.		
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.		
Hygiene measures	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.		
Environmental exposure controls	Environmental manager must be informed of all major releases.		

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Blue thixotropic gel.
Physical state	Liquid.
Form	Thixotropic gel.
Colour	Blue.
Odour	Sweet. Ethereal.
Odour threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not applicable.
Flash point	-17.0 °C (1.4 °F) Closed cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	4
Flammability limit - upper (%)	57
Vapour pressure	185 mmHg (20 °C/68 °F)
Vapour density	2 (Air = 1) (20 °C/68 °F)
Relative density	Heavy grade: 1.10 (20 °C/68 °F) Medium grade: 1.03 (20 °C/68 °F) Light grade: 0.95 (20 °C/68 °F)
Solubility(ies)	Slightly miscible.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not applicable.
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.
9.2. Other information	
Explosive limit	Not available.
VOC (Weight %)	25 - 50 (Hylomar Test Method 1.1A Determination of Volatile Matter)

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Risk of ignition. Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Heat, flames and sparks. Avoid temperatures exceeding the flash point.
10.5. Incompatible materials	Strong oxidising agents.
10.6. Hazardous decomposition products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: Toxicological information

Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation	Vapours may cause drowsiness and dizziness. In high concentrations, vapours may be irritating to the respiratory system.
Skin contact	Prolonged or repeated skin contact may cause drying, cracking, or irritation.
Eye contact	Causes serious eye irritation.
Ingestion	Ingestion may cause irritation and malaise.
Symptoms	Irritation of eyes and mucous membranes. Exposed individuals may experience eye tearing, redness, and discomfort. Vapours may cause drowsiness and dizziness.

11.1. Information on toxicological effects

Acute toxicity

General information

May cause discomfort if swallowed.

May cause disconnort it swallowed.		
Species	Test results	
Rabbit	20 ml/kg	
Rat	50 mg/l, 8 Hours	
Rat	5800 mg/kg	
Prolonged or repeated skin contact may cause drying, cracking, or irritation.		
Causes serious eye irritation.		
Based on available data, the classi	fication criteria are not met.	
Based on available data, the classi	fication criteria are not met.	
Based on available data, the classi	fication criteria are not met.	
Based on available data, the classi	fication criteria are not met.	
Based on available data, the classification criteria are not met.		
May cause drowsiness or dizziness	S.	
Based on available data, the classi	fication criteria are not met.	
Based on available data, the classi	fication criteria are not met.	
Not applicable.		
No other specific acute or chronic h	nealth impact noted.	
nformation		
The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.		
Species	Test results	
	Species Rabbit Rat Rat Prolonged or repeated skin contact Causes serious eye irritation. Based on available data, the classi May cause drowsiness or dizziness Based on available data, the classi Not applicable. No other specific acute or chronic h nformation The product is not classified as envipossibility that large or frequent spipers	

12.2. Persistence and degradability	No data available.
12.3. Bioaccumulative potential	
Partition coefficient n-octanol/water (log Kow) Acetone (CAS 67-64-1)	-0.24
Bioconcentration factor (BCF)	Not available.
12.4. Mobility in soil	No data available.
Mobility in general	The product is miscible with water. May spread in water systems.
12.5. Results of PBT and vPvB assessment	Not a PBT or vPvB substance or mixture.
12.6. Other adverse effects	The product contains a substance which has a photochemical ozone creation potential.

SECTION 13: Disposal considerations

13.1. Waste treatment methods	
Residual waste	Do not discharge into rivers, lakes, mountains, etc. because the product may affect the environment.
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.
EU waste code	16 03 05* The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Do not discharge into drains, water courses or onto the ground. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose of in accordance with local regulations.

SECTION 14: Transport information

ADR	
14.1. UN number	UN1133
14.2. UN proper shipping	Adhesives
name	
14.3. Transport hazard class	(es)
Class	3
Subsidiary risk	-
Label(s)	3
Hazard No. (ADR)	33
Tunnel restriction code	D/E
14.4. Packing group	Ш
14.5. Environmental hazards	No.
14.6. Special precautions	Read safety instructions, SDS and emergency procedures before handling.
for user	
RID	
14.1. UN number	UN1133
14.2. UN proper shipping	Adhesives
name	
14.3. Transport hazard class	(es)
Class	3
Subsidiary risk	-
Label(s)	3
14.4. Packing group	
14.5. Environmental hazards	
14.6. Special precautions	Read safety instructions, SDS and emergency procedures before handling.
for user	
ADN	101/ (00
14.1. UN number	UN1133
14.2. UN proper shipping	Adhesives
name	(00)
14.3. Transport hazard class	
Class	3
Subsidiary risk	-
Label(s)	3
14.4. Packing group	
14.5. Environmental hazards	NU.

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling. for user ΙΑΤΑ UN1133 14.1. UN number Adhesives 14.2. UN proper shipping name 14.3. Transport hazard class(es) Class 3 Subsidiary risk 3 Label(s) 14.4. Packing group Ш 14.5. Environmental hazards No. ERG Code 31 14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling. for user IMDG 14.1. UN number UN1133 ADHESIVES 14.2. UN proper shipping name 14.3. Transport hazard class(es) 3 Class Subsidiary risk _ 3 Label(s) 14.4. Packing group п 14.5. Environmental hazards Marine pollutant No. EmS F-E, S-D 14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling. for user 14.7. Transport in bulk Not applicable. according to Annex II of Marpol and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substanc	es that deplete the ozone layer,	, Annex I and II, as amended
Not listed.		

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.

- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Not listed.

```
Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA
Not listed.
```

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Acetone (CAS 67-64-1)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended

Not listed.

Directive 92/85/EEC: on the breastfeeding, as amended	safety and health of pregnant workers and workers who have recently given birth or are
Not listed.	
Other EU regulations	
0	jor accident hazards involving dangerous substances, as amended
Acetone (CAS 67-64-1)	
	otection of the health and safety of workers from the risks related to chemical agents at
Acetone (CAS 67-64-1)	
Directive 94/33/EC on the pr	otection of young people at work, as amended
Not listed.	
Other regulations	This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006. The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended and respective national laws implementing EC directives.
National regulations	Follow national regulation for work with chemical agents.
15.2. Chemical safety assessment	No Chemical Safety Assessment has been carried out.
SECTION 16: Other inform	nation
List of abbreviations	
	DNEL: Derived No-Effect Level.
	PNEC: Predicted No-Effect Concentration. LD50: Lethal Dose, 50%.
	LC50: Lethal Concentration, 50%.
References	HSDB® - Hazardous Substances Data Bank Registry of Toxic Effects of Chemical Substances (RTECS)
Information on evaluation method leading to the classification of mixture	The mixture is classified based on test data for physical hazards. The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available. For details, refer to Sections 9, 11 and 12.
Full text of any H-statements not written out in full under	
Sections 2 to 15	H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.
Training information	Follow training instructions when handling this material.
Disclaimer	The information in the sheet was written based on the best knowledge and experience currently available.