

SAFETY DATA SHEET

Revision Date 11-May-2020 Version 5

1. IDENTIFICATION

Product identifier

Product Name DECAL & ADHESIVE REMOVER 5 OZ.

Other means of identification

Product Code 80025

Recommended use of the chemical and restrictions on use
Recommended Use Adhesive Remover
Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

ITW Permatex 6875 Parkland Blvd. Solon, Ohio 44139 USA Telephone: 1-87-Permatex

(866) 732-9502

24-hour emergency phone number

Chem-Tel: 800-255-3924 International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address: mail@permatex.com

May Also Be Distributed by:

ITW Permatex Canada 101-2360 Bristol Circle

Oakville, ON Canada L6H 6M5 Telephone: (800) 924-6994

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Aspiration toxicity	Category 1

Label elements

Emergency Overview

Signal word Danger

May cause an allergic skin reaction May cause genetic defects

May cause cancer

May be fatal if swallowed and enters airways



Appearance Clear Physical state Aerosol **Odor** Citrus

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Avoid breathing dust/fume/gas/mist/vapors/spray Contaminated work clothing should not be allowed out of the workplace Wear protective gloves

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention Specific treatment (see .? on this label)

IF ON SKIN: Wash with plenty of soap and water

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

May be harmful in contact with skin. Causes mild skin irritation. Toxic to aquatic life with long lasting effects. Toxic to aquatic life.

Unknown acute toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
DISTILLATES (PETROLEUM),	64742-47-8	80-90
HYDROTREATED LIGHT		
PROPANE	74-98-6	3 - 7
D-LIMONENE	5989-27-5	3 - 7
BUTANE	106-97-8	3 - 7

4. FIRST AID MEASURES

Description of first aid measures

General advice Call 911 or emergency medical service. Remove and isolate contaminated clothing and

shoes.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact In case of contact with liquefied gas, thaw frosted parts with lukewarm water.

Inhalation Move victim to fresh air. If breathing is irregular or stopped, administer artificial respiration.

Administer oxygen if breathing is difficult.

Ingestion IF SWALLOWED:. Call a physician or poison control center immediately. Do NOT induce

vomiting.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved and take precautions to

protect themselves.

Most important symptoms and effects, both acute and delayed

See section 2 for more information. **Symptoms**

Indication of any immediate medical attention and special treatment needed

Keep victim warm and quiet. Note to physicians

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing agent suitable for type of surrounding fire, Dry chemical or CO2, Water spray, fog or regular foam, Move containers from fire area if you can do it without risk, Damaged cylinders should be handled only by specialists

Unsuitable extinguishing media

None

Specific hazards arising from the chemical

Some may burn but none ignite readily. Ruptured cylinders may rocket.

Explosion data

Sensitivity to Mechanical Impact None Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Do not touch or walk through spilled material. Stop leak if you can do it without risk.

Ventilate the area. Other Information

Environmental precautions

Environmental precautions Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to

contact spilled material. Prevent entry into waterways, sewers, basements or confined

areas.

Methods and material for containment and cleaning up

Methods for containment If possible, turn leaking containers so that gas escapes rather than liquid. Allow substance

to evaporate.

80025 - DECAL & ADHESIVE REMOVER 5 OZ.

Revision Date 11-May-2020

Methods for cleaning upDo not direct water at spill or source of leak.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not

puncture or incinerate cans. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage Conditions Store locked up. Do not expose to temperatures exceeding 50 °C/122 °F.

Incompatible materials Strong oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
PROPANE	: See Appendix F: Minimal	TWA: 1000 ppm	IDLH: 2100 ppm
74-98-6	Oxygen Content, explosion hazard	TWA: 1800 mg/m ³	TWA: 1000 ppm
		(vacated) TWA: 1000 ppm	TWA: 1800 mg/m ³
		(vacated) TWA: 1800 mg/m ³	_
BUTANE	STEL: 1000 ppm explosion	(vacated) TWA: 800 ppm	IDLH: 1600 ppm
106-97-8	hazard	(vacated) TWA: 1900 mg/m ³	TWA: 800 ppm
		, ,	TWA: 1900 mg/m ³

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of

equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state Aerosol Appearance Clear Odor Citrus

Odor threshold No information available

Values Remarks • Method Property

pН No information available Melting point / freezing point No information available Boiling point / boiling range No information available -104 °C / -155 °F Flash point

Gives a flame projection at full valve opening or flashback at any degree of valve opening

Evaporation rate No information available Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit: 6.6% Lower flammability limit: 0.9%

Vapor pressure 30-44 psig @70°F/55-75 psig @ 130°F

Vapor density No information available

Relative density 0.769

Insoluble in water Water solubility Solubility(ies) No information available **Partition coefficient** No information available **Autoignition temperature** No information available **Decomposition temperature** No information available Kinematic viscosity No information available Dynamic viscosity No information available **Explosive properties** No information available **Oxidizing properties** No information available

Other Information

Softening point No information available Molecular weight No information available

VOC Content (%)

Density No information available **Bulk density** No information available SADT (self-accelerating No information available

decomposition temperature)

10. STABILITY AND REACTIVITY

Reactivity

No information available

Chemical stability

Stable under normal conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks. Temperatures >50 °C / 122 °F.

Incompatible materials

Strong oxidizing agents

Hazardous Decomposition Products

Carbon oxides

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation May cause irritation of respiratory tract.

Eye contact Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.

Ingestion Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and

pneumonitis.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat)4 h
64742-47-8			
PROPANE	-	-	> 800000 ppm (Rat) 15 min
74-98-6			
D-LIMONENE	= 5200 mg/kg (Rat) = 4400 mg/kg	> 5 g/kg (Rabbit)	-
5989-27-5	(Rat)		
BUTANE	-	-	= 658 g/m³ (Rat) 4 h
106-97-8			

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

SensitizationNo information available. **Germ cell mutagenicity**No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
D-LIMONENE	-	Group 3	-	X
5989-27-5				

IARC (International Agency for Research on Cancer)

Not classifiable as a human carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Target Organ Effects Central nervous system.

The following values are calculated based on chapter 3.1 of the GHS document .

 ATEmix (oral)
 6256 mg/kg

 ATEmix (dermal)
 2430 mg/kg

 ATEmix (inhalation-gas)
 1936270 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

2 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical Name	Partition coefficient
PROPANE	2.3
74-98-6	
BUTANE	2.89
106-97-8	

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS	

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number D001

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
D-LIMONENE	Toxic
5989-27-5	

14. TRANSPORT INFORMATION

DOT

UN/ID No 1950

Proper shipping name: Aerosols, Limited Quantity (LQ)

Hazard Class 2.1 Emergency Response Guide 126

Number

IATA

UN/ID No ID 8000

Proper shipping name: Consumer commodity

Hazard Class 9 ERG Code 9L

IMDG

UN/ID No 1950

Proper shipping name: Aerosols, Limited Quantity (LQ)

Hazard Class 2.1 EmS-No F-D, S-U

15. REGULATORY INFORMATION

International Inventories

TSCA Complies DSL/NDSL Complies Complies **EINECS/ELINCS** Complies **ENCS IECSC** Complies Complies **KECL PICCS** Complies **AICS** Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
PROPANE	X	X	X
74-98-6			
BUTANE	X	X	X
106-97-8			

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

A Compressed gases, B5 - Flammable aerosol, D2B - Toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPAHealth hazards2Flammability4Instability0-HMISHealth hazards2Flammability4Physical hazards0Personal protectionB

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date 11-May-2020

Disclaimer

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

End of Safety Data Sheet