



# SAFETY DATA SHEET

Revision Date 11-May-2020

Version 8

## 1. IDENTIFICATION

### Product identifier

**Product Name** 127MA DISC BRAKE QUIET 9OZ AE

### Other means of identification

**Product Code** 80077

### Recommended use of the chemical and restrictions on use

**Recommended Use** Adhesive

**Uses advised against** No information available

### Details of the supplier of the safety data sheet

#### Manufacturer Address

ITW Permatex  
6875 Parkland Blvd.  
Solon, Ohio 44139 USA  
Telephone: 1-87-Permatex  
(866) 732-9502

#### 24-hour emergency phone number

Chem-Tel: 800-255-3924  
International Emergency:  
00+1+ 813-248-0585  
Contract Number: MIS0003453

#### May Also Be Distributed by:

ITW Permatex Canada  
101-2360 Bristol Circle  
Oakville, ON Canada L6H 6M5  
Telephone: (800) 924-6994

**E-mail address:** mail@permatex.com

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1

### Label elements

#### **Emergency Overview**

#### **Signal word**

**Danger**

Causes skin irritation  
Causes serious eye irritation

May cause genetic defects  
May cause cancer  
Suspected of damaging fertility or the unborn child  
May cause respiratory irritation  
May cause drowsiness or dizziness  
May cause damage to organs through prolonged or repeated exposure  
May be fatal if swallowed and enters airways



**Appearance** Blue

**Physical state** Flammable Aerosol

**Odor** Solvent

#### **Precautionary Statements - Prevention**

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Use personal protective equipment as required  
Wash face, hands and any exposed skin thoroughly after handling  
Wear eye/face protection  
Do not breathe dust/fume/gas/mist/vapors/spray  
Use only outdoors or in a well-ventilated area

#### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention  
Specific treatment (see .? on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
If eye irritation persists: Get medical advice/attention  
IF ON SKIN: Wash with plenty of soap and water  
If skin irritation occurs: Get medical advice/attention  
Take off contaminated clothing and wash before reuse  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
Do NOT induce vomiting

#### **Precautionary Statements - Storage**

Store locked up  
Store in a well-ventilated place. Keep container tightly closed

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### **Hazards not otherwise classified (HNOC)**

Not applicable

#### **Other Information**

Harmful to aquatic life with long lasting effects. Harmful to aquatic life.

Unknown acute toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
ACETONE	67-64-1	15 - 40
PROPANE	74-98-6	10 - 30
N-HEXANE	110-54-3	10 - 30
BUTANE	106-97-8	10 - 30
ISO-HEXANE	107-83-5	5 - 10
ETHYL ACETATE	141-78-6	5 - 10
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPH.	64742-89-8	1 - 5
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC	64742-53-6	0.1 - 1

### 4. FIRST AID MEASURES

#### Description of first aid measures

<b>General advice</b>	Call 911 or emergency medical service. Remove and isolate contaminated clothing and shoes.
<b>Eye contact</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
<b>Skin contact</b>	In case of contact with liquefied gas, thaw frosted parts with lukewarm water.
<b>Inhalation</b>	Move victim to fresh air. If breathing is irregular or stopped, administer artificial respiration. Administer oxygen if breathing is difficult.
<b>Ingestion</b>	IF SWALLOWED: Call a physician or poison control center immediately. Do NOT induce vomiting.
<b>Self-protection of the first aider</b>	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

#### Most important symptoms and effects, both acute and delayed

**Symptoms** See section 2 for more information.

#### Indication of any immediate medical attention and special treatment needed

**Note to physicians** Keep victim warm and quiet.

### 5. FIRE-FIGHTING MEASURES

#### Suitable extinguishing media

Use extinguishing agent suitable for type of surrounding fire, Dry chemical or CO<sub>2</sub>, Water spray, fog or regular foam, Move containers from fire area if you can do it without risk, Damaged cylinders should be handled only by specialists

#### Unsuitable extinguishing media

None

#### Specific hazards arising from the chemical

Some may burn but none ignite readily. Ruptured cylinders may rocket.

#### Explosion data

**Sensitivity to Mechanical Impact** None.  
**Sensitivity to Static Discharge** None.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Do not touch or walk through spilled material. Stop leak if you can do it without risk.  
**Other Information** Ventilate the area.

**Environmental precautions**

**Environmental precautions** Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material. Prevent entry into waterways, sewers, basements or confined areas.

**Methods and material for containment and cleaning up**

**Methods for containment** If possible, turn leaking containers so that gas escapes rather than liquid. Allow substance to evaporate.  
**Methods for cleaning up** Do not direct water at spill or source of leak.  
**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Advice on safe handling** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Contents under pressure. Do not puncture or incinerate cans. Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wash thoroughly after handling. Wash contaminated clothing before reuse. Do not stick pin or any other sharp object into opening on top of can.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Store locked up. Do not expose to temperatures exceeding 50 °C/122 °F.  
**Incompatible materials** Strong oxidizing agents, Nitrates, Fluorine, Chlorine

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters****Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ACETONE 67-64-1	STEL: 500 ppm TWA: 250 ppm	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup> (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m <sup>3</sup> (vacated) STEL: 2400 mg/m <sup>3</sup> The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors.	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m <sup>3</sup>

		(vacated) STEL: 1000 ppm	
PROPANE 74-98-6	: See Appendix F: Minimal Oxygen Content, explosion hazard	TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup> (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m <sup>3</sup>	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup>
N-HEXANE 110-54-3	TWA: 50 ppm S*	TWA: 500 ppm TWA: 1800 mg/m <sup>3</sup> (vacated) TWA: 50 ppm (vacated) TWA: 180 mg/m <sup>3</sup>	IDLH: 1100 ppm TWA: 50 ppm TWA: 180 mg/m <sup>3</sup>
BUTANE 106-97-8	STEL: 1000 ppm explosion hazard	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m <sup>3</sup>	IDLH: 1600 ppm TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup>
ISO-HEXANE 107-83-5	STEL: 1000 ppm TWA: 500 ppm	-	-
ETHYL ACETATE 141-78-6	TWA: 400 ppm	TWA: 400 ppm TWA: 1400 mg/m <sup>3</sup> (vacated) TWA: 400 ppm (vacated) TWA: 1400 mg/m <sup>3</sup>	IDLH: 2000 ppm TWA: 400 ppm TWA: 1400 mg/m <sup>3</sup>

NIOSH IDLH *Immediately Dangerous to Life or Health*

**Other Information** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

### Appropriate engineering controls

**Engineering Controls** Showers  
Eyewash stations  
Ventilation systems

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin and body protection** Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

**Respiratory protection** Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

**Physical state** Flammable Aerosol  
**Appearance** Blue  
**Odor** Solvent  
**Odor threshold** No information available

**Property** **Values**  
pH No information available  
Melting point / freezing point No information available  
Boiling point / boiling range 83 °C / 181 °F  
Flash point -104 °C / -155 °F

### Remarks • Method

Gives a flame projection at full valve opening or flashback at any degree of valve opening

**Evaporation rate** No information available  
**Flammability (solid, gas)** No information available  
**Flammability Limit in Air**  
Upper flammability limit: 10.2%  
Lower flammability limit: 2.4%  
**Vapor pressure** No information available  
**Vapor density** No information available  
**Relative density** 0.62

<b>Water solubility</b>	No information available
<b>Solubility(ies)</b>	No information available
<b>Partition coefficient</b>	No information available
<b>Autoignition temperature</b>	382 °C / 720 °F
<b>Decomposition temperature</b>	No information available
<b>Kinematic viscosity</b>	No information available
<b>Dynamic viscosity</b>	No information available
<b>Explosive properties</b>	Not an explosive
<b>Oxidizing properties</b>	No information available

**Other Information**

<b>Softening point</b>	No information available
<b>Molecular weight</b>	No information available
<b>VOC Content (%)</b>	89
<b>Density</b>	No information available
<b>Bulk density</b>	No information available
<b>SADT (self-accelerating decomposition temperature)</b>	No information available

## 10. STABILITY AND REACTIVITY

**Reactivity**

No information available

**Chemical stability**

Stable under normal conditions

**Possibility of Hazardous Reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Strong oxidizing agents, Nitrates, Fluorine, Chlorine

**Hazardous Decomposition Products**

Carbon oxides

## 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure**

<b>Inhalation</b>	May cause damage to organs through prolonged or repeated exposure if inhaled. May cause drowsiness or dizziness.
<b>Eye contact</b>	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.
<b>Skin contact</b>	May cause skin irritation and/or dermatitis.
<b>Ingestion</b>	Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
ACETONE 67-64-1	= 5800 mg/kg ( Rat )	> 15700 mg/kg ( Rabbit )	= 50100 mg/m <sup>3</sup> ( Rat ) 8 h
PROPANE 74-98-6	-	-	> 800000 ppm ( Rat ) 15 min
N-HEXANE 110-54-3	= 25 g/kg ( Rat )	= 3000 mg/kg ( Rabbit )	= 48000 ppm ( Rat ) 4 h
BUTANE 106-97-8	-	-	= 658 g/m <sup>3</sup> ( Rat ) 4 h

ETHYL ACETATE 141-78-6	= 5620 mg/kg ( Rat )	> 18000 mg/kg ( Rabbit ) > 20 mL/kg ( Rabbit )	= 4000 ppm ( Rat ) 4 h
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPH. 64742-89-8	-	= 3000 mg/kg ( Rabbit )	-
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC 64742-53-6	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	= 2180 mg/m <sup>3</sup> ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** No information available.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** No information available.

**Germ cell mutagenicity** No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC 64742-53-6	A2	Group 1	Known	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

**Target Organ Effects** Central nervous system, Eyes, Peripheral Nervous System (PNS), Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	14249 mg/kg
ATEmix (dermal)	12716 mg/kg
ATEmix (inhalation-gas)	1049349 mg/l
ATEmix (inhalation-dust/mist)	283.9 mg/l
ATEmix (inhalation-vapor)	48484.8 mg/l

## 12. ECOLOGICAL INFORMATION

This product contains a chemical which is listed as a marine pollutant according to DOT.

**Ecotoxicity**

8.8 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility**

No information available.

Chemical Name	Partition coefficient
ACETONE 67-64-1	-0.24
PROPANE	2.3

74-98-6	
BUTANE 106-97-8	2.89
ETHYL ACETATE 141-78-6	0.6

**Other adverse effects**

No information available

**13. DISPOSAL CONSIDERATIONS****Waste treatment methods**

<b>Disposal of wastes</b>	Disposal should be in accordance with applicable regional, national and local laws and regulations.
<b>Contaminated packaging</b>	Do not reuse container.
<b>US EPA Waste Number</b>	D001, U002 U112

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
ACETONE 67-64-1	Ignitable
N-HEXANE 110-54-3	Toxic Ignitable
ETHYL ACETATE 141-78-6	Toxic Ignitable

**14. TRANSPORT INFORMATION****DOT**

<b>UN/ID No</b>	1950
<b>Proper shipping name:</b>	Aerosols, Limited Quantity (LQ)
<b>Hazard Class</b>	2.1
<b>Marine pollutant</b>	This product contains a chemical which is listed as a marine pollutant according to DOT.
<b>Emergency Response Guide Number</b>	126

**IATA**

<b>UN/ID No</b>	ID 8000
<b>Proper shipping name:</b>	Consumer commodity
<b>Hazard Class</b>	9
<b>ERG Code</b>	9L

**IMDG**

<b>UN/ID No</b>	1950
<b>Proper shipping name:</b>	Aerosols, Limited Quantity (LQ)
<b>Hazard Class</b>	2.1
<b>EmS-No</b>	F-D, S-U
<b>Marine pollutant</b>	This product contains a chemical which is listed as a marine pollutant according to IMDG/IMO.

**15. REGULATORY INFORMATION****International Inventories**

<b>TSCA</b>	Complies
<b>DSL/NDL</b>	Complies



<b>EINECS/ELINCS</b>	Not determined
<b>ENCS</b>	Not determined
<b>IECSC</b>	Not determined
<b>KECL</b>	Not determined
<b>PICCS</b>	Not determined
<b>AICS</b>	Not determined

**Legend:**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**IECSC** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

**US Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
N-HEXANE - 110-54-3	1.0

**SARA 311/312 Hazard Categories**

<b>Acute health hazard</b>	Yes
<b>Chronic Health Hazard</b>	Yes
<b>Fire hazard</b>	Yes
<b>Sudden release of pressure hazard</b>	No
<b>Reactive Hazard</b>	No

**CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
ACETONE 67-64-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
N-HEXANE 110-54-3	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
ETHYL ACETATE 141-78-6	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

**US State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
N-HEXANE 110-54-3	Developmental

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ACETONE 67-64-1	X	X	X
PROPANE 74-98-6	X	X	X
BUTANE 106-97-8	X	X	X
N-HEXANE	X	X	X

110-54-3			
ETHYL ACETATE 141-78-6	X	X	X
ISO-HEXANE 107-83-5	X	X	X
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC 64742-53-6	-	X	-

**U.S. EPA Label Information**

**EPA Pesticide Registration Number** Not applicable

**WHMIS Hazard Class**

D2B - Toxic materials, D2A - Very toxic materials

**16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION**

<b>NFPA</b>	<b>Health hazards</b> 2	<b>Flammability</b> 3	<b>Instability</b> 0	-
<b>HMIS</b>	<b>Health hazards</b> 2	<b>Flammability</b> 3	<b>Physical hazards</b> 0	<b>Personal protection</b> B

NFPA (National Fire Protection Association)  
HMIS (Hazardous Material Information System)

**Revision Date** 11-May-2020

**Disclaimer**

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

**End of Safety Data Sheet**