

Revision Date 03-May-2019

SAFETY DATA SHEET

Version 5

1. IDENTIFICATION

Product identifier Product Name

83H SUPER 300 FORM- A- GASKET SEALANT .25PT

Other means of identification Product Code

Recommended use of the chemical and restrictions on useRecommended UseSealantUses advised againstNo information available

80057

Details of the supplier of the safety data sheet Manufacturer Address ITW Permatex 6875 Parkland Blvd. Solon, Ohio 44139 USA Telephone: 1-87-Permatex (866) 732-9502 24-hour emergency phone number Chem-Tel: 800-255-3924 International Emergency: 00+1+ 813-248-0585 Contract Number: MIS0003453

E-mail address: mail@permatex.com

May Also Be Distributed by: ITW Permatex Canada 101-2360 Bristol Circle Oakville, ON Canada L6H 6M5 Telephone: (800) 924-6994

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 3

Label elements

Emergency Overview

<u>Signal word</u> Warning

Causes serious eye irritation May cause an allergic skin reaction Suspected of causing cancer May cause drowsiness or dizziness Flammable liquid and vapor



Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Avoid breathing dust/fume/gas/mist/vapors/spray Wash face, hands and any exposed skin thoroughly after handling Contaminated work clothing should not be allowed out of the workplace Use only outdoors or in a well-ventilated area Keep away from heat/sparks/open flames/hot surfaces. - No smoking Keep container tightly closed Use non-sparking tools Take precautionary measures against static discharge

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor/physician if you feel unwell

Precautionary Statements - Storage

Store locked up Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Not applicable

Unknown acute toxicity

2.0508 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
2-PROPANOL	67-63-0	15 - 40
FUMARATED RESIN	65997-04-8	10 - 30
TALC	14807-96-6	7 - 13
CARBON BLACK	1333-86-4	0.1 - 1

4. FIRST AID MEASURES

Description of first aid measures

General advice	Get medical advice/attention if you feel unwell.		
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.		
Skin contact	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash with soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.		
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.		
Ingestion	IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician.		
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.		
Most important symptoms and effe	cts, both acute and delayed		
Symptoms	May cause allergic skin reaction.		
Indication of any immediate medica	al attention and special treatment needed		
Note to physicians	Treat symptomatically.		
5. FIRE-FIGHTING MEASURES			
<u>Suitable extinguishing media</u> Carbon dioxide (CO2), Dry chemical, Foam			
<u>Unsuitable extinguishing media</u> None			

<u>Specific hazards arising from the chemical</u> Flammable. Risk of ignition. Vapors may travel to source of ignition and flash back.

Explosion dataSensitivity to Mechanical ImpactNone.Sensitivity to Static DischargeNone.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautionsEnsure adequate ventilation, especially in confined areas. Avoid contact with skin, eyes or
clothing. Use personal protective equipment as required. Remove all sources of ignition.

Environmental precautions

Environmental precautions	See Section 12 for additional Ecological Information.		
Methods and material for containm	Methods and material for containment and cleaning up		
Methods for containment	Prevent further leakage or spillage if safe to do so.		
Methods for cleaning up	Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.		
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.		
7. HANDLING AND STORAGE			

Precautions for safe handling

Advice on safe handling	Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.
	Take precautionary measures against static discharges. Remove all sources of ignition. Keep away from heat/sparks/open flames/hot surfaces No smoking.

Conditions for safe storage, including any incompatibilities			
Storage Conditions	Keep tightly closed in a dry and cool place. Store locked up.		
Incompatible materials Strong oxidizing agents			

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
2-PROPANOL	STEL: 400 ppm	TWA: 400 ppm	IDLH: 2000 ppm
67-63-0	TWA: 200 ppm	TWA: 980 mg/m ³	TWA: 400 ppm
		(vacated) TWA: 400 ppm	TWA: 980 mg/m ³
		(vacated) TWA: 980 mg/m ³	STEL: 500 ppm
		(vacated) STEL: 500 ppm	STEL: 1225 mg/m ³
		(vacated) STEL: 1225 mg/m ³	
TALC	TWA: 2 mg/m ³ particulate matter	(vacated) TWA: 2 mg/m ³ respirable	IDLH: 1000 mg/m ³
14807-96-6	containing no asbestos and <1%	dust <1% Crystalline silica,	TWA: 2 mg/m ³ containing no
	crystalline silica, respirable	containing no Asbestos	Asbestos and <1% Quartz
	particulate matter	TWA: 20 mppcf if 1% Quartz or	respirable dust
		more;use Quartz limit	
CARBON BLACK	TWA: 3 mg/m ³ inhalable particulate	TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³
1333-86-4	matter	(vacated) TWA: 3.5 mg/m ³	TWA: 3.5 mg/m ³
			TWA: 0.1 mg/m ³ Carbon black in
			presence of Polycyclic aromatic
			hydrocarbons PAH

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls

Showers Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles).	
Skin and body protection	Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.	
Respiratory protection	Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.	
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.	

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Paste	
Appearance	Black	
Odor	Alcohol	
Odor threshold	No information available	
Property_	Values	Remarks • Method
рН	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	82 °C / 180 °F	
Flash point	25 °C / 77 °F	Tag Closed Cup
Evaporation rate	>1	Ether = 1
Flammability (solid, gas) Flammability Limit in Air	No information available	
Upper flammability limit:	12.0%	
Lower flammability limit:	2.0%	
Vapor pressure	33 mm Hg @ 68°F	
Vapor density	2.07	Air = 1
Relative density	1.0	, ui — 1
Water solubility	Partially soluble	
Solubility(ies)	No information available	
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	
Other Information		
Softening point	No information available	
Molecular weight	No information available	
VOC Content (%)	38.6%	
Density	No information available	
Bulk density	No information available	
SADT (self-accelerating	No information available	
decomposition temperature)		

10. STABILITY AND REACTIVITY

Reactivity

No information available

<u>Chemical stability</u> Stable under normal conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks. Take precautionary measures against static discharges.

Incompatible materials Strong oxidizing agents

Hazardous Decomposition Products

Carbon oxides Aldehydes Carboxylic acids

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation	May cause irritation of respiratory tract. May cause drowsiness or dizziness.
Eye contact	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.
Skin contact	May cause skin irritation and/or dermatitis. May cause sensitization by skin contact.
Ingestion	Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
2-PROPANOL	5050 mg/kg	12800 mg/kg	= 72600 mg/m ³ (Rat) 4 h
67-63-0			
FUMARATED RESIN	> 2000 mg/kg (Rat)	-	-
65997-04-8			
CARBON BLACK	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-
1333-86-4			

Information on toxicological effects

Symptoms

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization Germ cell mutagenicity		information available.				
Carcinogenicity		The table below indicates whether each agency has listed any ingredient as a carcinogen.				
Chemical Name	ACGIH	I IARC	NTP	OSHA		
TALC 14807-96-6	-	Group 3	-	X		
CARBON BLACK 1333-86-4	A3	Group 2B	-	Х		
X - Present	o Humans sinogenic to Huma an carcinogen afety and Health J	Administration of the US Department		-		
Target Organ Effects Central Vascular System (CVS), Eyes, Respiratory system, Skin, Thyroid.						
The following values are calculated based on chapter 3.1 of the GHS document . ATEmix (oral) 13750 mg/kg ATEmix (dermal) 9924 mg/kg ATEmix (inhalation-dust/mist) 115.1 mg/l						

12. ECOLOGICAL INFORMATION

Ecotoxicity

0.06 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical Name	Partition coefficient
2-PROPANOL	0.05
67-63-0	

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes	This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).
Contaminated packaging	Do not reuse container.
US EPA Waste Number	D001

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
2-PROPANOL	Toxic
67-63-0	Ignitable

14. TRANSPORT INFORMATION

DOT UN/ID No Proper shipping name: Hazard Class Packing Group Emergency Response Guide Number	1866 Resin, solution, flammable, Limited Quantity (LQ) 3 III 127
IATA UN/ID No Proper shipping name: Hazard Class ERG Code	ID8000 Consumer commodity 9 9L
IMDG_ UN/ID No Proper shipping name: Hazard Class	1866 Resin, solution, flammable, Limited Quantity (LQ) 3

Packing Group	111
EmS-No	F-E, S-E

1	15.	REG	JLAT	ORY	INFC	ORMA	TION
. 112				••••			

International Inventories	
TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Not determined
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Not determined

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
2-PROPANOL - 67-63-0	1.0
SARA 311/312 Hazard Categories	
Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65	
CARBON BLACK - 1333-86-4	*Carcinogen (airborne, unbound particles of respirable size)	

• *The asterisked chemical(s) listed are not subject to Proposition 65 because they are not airborne in the finished product U.S. State Right-to-Know Regulations

Γ	Chemical Name	New Jersey	Massachusetts	Pennsylvania

80057 - 83H SUPER 300 FORM- A- GASKET SEALANT .25PT

2-PROPANOL 67-63-0	Х	X	Х
TALC 14807-96-6	Х	X	Х
WATER 7732-18-5	-	-	Х
CARBON BLACK 1333-86-4	Х	X	Х

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

B2 - Flammable liquid, D2B - Toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health hazards	2	Flammability	3
HMIS	Health hazards	2	Flammability	3

Instability 0 -Physical hazards 0 Personal p

Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date 03-May-2019

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet