

**Safety Data Sheet**

according to UK REACH Regulation

Revision date: 10.05.2021

**Multi Signum Spray**

Page 1 of 14

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Multi Signum Spray 400ml lith.

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Lubricant

**1.3. Details of the supplier of the safety data sheet**

Company name:	Winkel GmbH	
Street:	Lisztstr. Nr.1	
Place:	53881 Euskirchen	
Telephone:	+49 (0) 22517769400-401	Telefax:+49 (0) 22517769402
e-mail:	info@winkelgroup.de	
Internet:	www.winkelgroup.de	

**1.4. Emergency telephone number:** 111 NHS (National Health Service)**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Hazard categories:

Aerosol: Aerosol 1

Aspiration hazard: Asp. Tox. 1

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

May be fatal if swallowed and enters airways.

May cause drowsiness or dizziness.

**2.2. Label elements****GB CLP Regulation****Hazard components for labelling**

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, &lt;2% aromatics

**Signal word:** Danger**Pictograms:****Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H336	May cause drowsiness or dizziness.

**Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.

## Safety Data Sheet

according to UK REACH Regulation

# Multi Signum Spray

Revision date: 10.05.2021

Page 2 of 14

P271	Use only outdoors or in a well-ventilated area.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

### Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

### 2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.  
The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
75-28-5	isobutane			50 - <= 100 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Liquefied gas; H220 H280			
1174921-73-3	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics			20 - < 25 %
	927-241-2		01-2119471843-32	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 3; H226 H336 H304 H412 EUH066			
74-98-6	propane			5 - < 10 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Liquefied gas; H220 H280			
64742-48-9	Naphtha Petroleum Hydro treated Heavy			5 - < 10 %
	918-481-9		01-2119457273-39	
	Asp. Tox. 1; H304 EUH066			
106-97-8	butane			1 - < 3 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Liquefied gas; H220 H280			
1471316-72-9	Benzenesulfonic acids, di-C10-14-alkyl derivatives, calcium salts			< 0.1 %
	939-603-7		01-2119978241-36	
	Skin Sens. 1B; H317			

Full text of H and EUH statements: see section 16.

**Safety Data Sheet**

according to UK REACH Regulation

**Multi Signum Spray**

Revision date: 10.05.2021

Page 3 of 14

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
75-28-5	200-857-2	isobutane	50 - <= 100 %
		inhalation: LC50 = 1237 mg/l (vapours)	
1174921-73-3	927-241-2	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	20 - < 25 %
		inhalation: LC50 = > 4951 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 15000 mg/kg	
64742-48-9	918-481-9	Naphtha Petroleum Hydro treated Heavy	5 - < 10 %
		inhalation: LC50 = 4951 mg/l (vapours); dermal: LD50 = >3160 mg/kg; oral: LD50 = >8000 mg/kg	
106-97-8	203-448-7	butane	1 - < 3 %
		inhalation: LC50 = 658 ppm (gases)	
1471316-72-9	939-603-7	Benzenesulfonic acids, di-C10-14-alkyl derivatives, calcium salts	< 0.1 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 10000 - < 20000 mg/kg Skin Sens. 1B; H317: >= 10 - 100	

**Labelling for contents according to Regulation (EC) No 648/2004**

&gt;= 30 % aliphatic hydrocarbons, perfumes.

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

**After inhalation**

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

**After contact with skin**

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

**After contact with eyes**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

**After ingestion**

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

**4.2. Most important symptoms and effects, both acute and delayed**

Headache, nausea, dizziness, fatigue, skin irritation

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Water fog. Foam. Carbon dioxide (CO<sub>2</sub>). Extinguishing powder.

**Unsuitable extinguishing media**

Full water jet

**5.2. Special hazards arising from the substance or mixture**

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO<sub>2</sub>, aldehydes and soot. These can be very dangerous if they are inhaled in high

**Safety Data Sheet**

according to UK REACH Regulation

Revision date: 10.05.2021

**Multi Signum Spray**

Page 4 of 14

concentrations or in enclosed spaces.

**5.3. Advice for firefighters**

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Danger of bursting container.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General measures**

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Wear personal protection equipment.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

**6.3. Methods and material for containment and cleaning up****Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

**6.4. Reference to other sections**

Safe handling: see section 7  
Personal protection equipment: see section 8  
Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Observe instructions for use.  
Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.  
When using do not eat, drink, smoke, sniff.  
Wear personal protection equipment (refer to section 8).  
In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

**Advice on general occupational hygiene**

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

**Further information on handling**

Avoid contact with skin and eyes.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed. Observe legal regulations and provisions.

**Hints on joint storage**

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

**Further information on storage conditions**

Protect from frost. Protect from direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

## Safety Data Sheet

according to UK REACH Regulation

# Multi Signum Spray

Revision date: 10.05.2021

Page 5 of 14

### 7.3. Specific end use(s)

No information available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

#### DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
1174921-73-3	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics			
	Worker DNEL, long-term	inhalation	systemic	871 mg/m <sup>3</sup>
	Worker DNEL, long-term	dermal	systemic	77 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	185 mg/m <sup>3</sup>
	Consumer DNEL, long-term	dermal	systemic	46 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	46 mg/kg bw/day
1471316-72-9	Benzenesulfonic acids, di-C10-14-alkyl derivatives, calcium salts			
	Worker DNEL, long-term	inhalation	systemic	35,26 mg/m <sup>3</sup>
	Worker DNEL, long-term	dermal	systemic	25 mg/kg bw/day
	Worker DNEL, acute	dermal	local	1,04 mg/cm <sup>2</sup>
	Consumer DNEL, long-term	inhalation	systemic	8,7 mg/m <sup>3</sup>
	Consumer DNEL, long-term	dermal	systemic	12,5 mg/kg bw/day
	Consumer DNEL, acute	dermal	local	0,518 mg/cm <sup>2</sup>
	Consumer DNEL, long-term	oral	systemic	2,5 mg/kg bw/day

#### PNEC values

CAS No	Substance	Value
1471316-72-9	Benzenesulfonic acids, di-C10-14-alkyl derivatives, calcium salts	
	Freshwater	0,1 mg/l
	Freshwater (intermittent releases)	1 mg/l
	Marine water	0,1 mg/l
	Freshwater sediment	45211 mg/kg
	Marine sediment	45211 mg/kg
	Micro-organisms in sewage treatment plants (STP)	1000 mg/l
	Soil	36739,74 mg/kg

#### Additional advice on limit values

a no restriction

b End of exposure or end of shift

**Safety Data Sheet**

according to UK REACH Regulation

**Multi Signum Spray**

Revision date: 10.05.2021

Page 6 of 14

c at long-term exposure:  
d before next shift

blood (B)  
Urine (U)

**8.2. Exposure controls****Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Suitable eye protection: Tightly sealed safety glasses.  
DIN EN 166

**Hand protection**

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time: 480min

Thickness of the glove material 0,45 mm

EN ISO 374

**Skin protection**

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

**Respiratory protection**

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

When exceeding the relevant workplace exposure limits, note the following:

Suitable respiratory protective equipment: Combination filter device (DIN EN 141)..

Filtering device with filter or ventilator filtering device of type: AX

Observe the wear time limits as specified by the manufacturer.

Observe legal regulations and provisions.

**Environmental exposure controls**

Observe legal regulations and provisions.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state: Aerosol  
Colour: brown  
Odour: sweetish

**Test method****Changes in the physical state**

Boiling point or initial boiling point and boiling range: -42 °C

Flash point: > 23 °C

Lower explosion limits: 0,6

Upper explosion limits: 9,4

pH-Value (at 20 °C): DIN 19268

Viscosity / kinematic: < 7 mm<sup>2</sup>/s

Density (at 20 °C): 0,7828 g/cm<sup>3</sup> DIN 51757

**9.2. Other information**

## Safety Data Sheet

according to UK REACH Regulation

Revision date: 10.05.2021

# Multi Signum Spray

Page 7 of 14

### Other safety characteristics

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No information available.

### 10.2. Chemical stability

The product is stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

### 10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

### 10.6. Hazardous decomposition products

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO<sub>2</sub>, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

### Further information

Do not mix with other chemicals.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in GB CLP Regulation

#### Toxicokinetics, metabolism and distribution

There are no data available on the mixture itself.

#### Acute toxicity

Based on available data, the classification criteria are not met.

## Safety Data Sheet

according to UK REACH Regulation

# Multi Signum Spray

Revision date: 10.05.2021

Page 8 of 14

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
75-28-5	isobutane				
	inhalation vapour	LC50 1237 mg/l	Mouse.		
1174921-73-3	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 > 15000 mg/kg	Rat	Study report (1977)	OECD Guideline 423
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1993)	OECD Guideline 402
	inhalation (4 h) vapour	LC50 > 4951 mg/l	Rat		
64742-48-9	Naphtha Petroleum Hydro treated Heavy				
	oral	LD50 >8000 mg/kg	Rat		
	dermal	LD50 >3160 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 4951 mg/l	Rat		
106-97-8	butane				
	inhalation (4 h) gas	LC50 658 ppm	Rat	GESTIS	
1471316-72-9	Benzenesulfonic acids, di-C10-14-alkyl derivatives, calcium salts				
	oral	LD50 > 10000 - < 20000 mg/kg	Rat	Study report (1972)	Adult albino male Sprague-Dawley rats
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1989)	OECD Guideline 402

### Irritation and corrosivity

Based on available data, the classification criteria are not met.

### Sensitising effects

Based on available data, the classification criteria are not met.

### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

### STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics)

### STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

### Aspiration hazard

May be fatal if swallowed and enters airways.

### Specific effects in experiment on an animal

No information available.

### Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].



## Safety Data Sheet

according to UK REACH Regulation

Revision date: 10.05.2021

### Multi Signum Spray

Page 9 of 14

#### SECTION 12: Ecological information

##### 12.1. Toxicity

There are no data available on the mixture itself.

## Safety Data Sheet

according to UK REACH Regulation

### Multi Signum Spray

Revision date: 10.05.2021

Page 10 of 14

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
75-28-5	isobutane					
	Acute fish toxicity	LC50 mg/l	91,42	96 h	Fish, no other information	United States Environmental Protection A The Ecosar class program has been develo
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200) Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200) Calculation using ECOSAR Program v1.00.
1174921-73-3	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics					
	Acute fish toxicity	LC50 mg/l	>1000	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50 mg/l	>1000	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50 mg/l	>1000	48 h	Daphnia magna	
	Fish toxicity	NOEC mg/l	0,182	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010) The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC mg/l	0,317	21 d	Daphnia magna	Company report (2010) The aquatic toxicity was estimated by a
74-98-6	propane					
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A The Ecosar class program has been develo
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200) Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200) Calculation using ECOSAR Program v1.00.
64742-48-9	Naphtha Petroleum Hydro treated Heavy					
	Acute fish toxicity	LC50 mg/l	>1000	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50 mg/l	>1000	96 h	Scenedesmus subspicatus	
	Acute crustacea toxicity	EC50 mg/l	>1000	48 h	Daphnia magna	
106-97-8	butane					
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A The Ecosar class program has been develo
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200) Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200) Calculation using ECOSAR Program v1.00.

## Safety Data Sheet

according to UK REACH Regulation

### Multi Signum Spray

Revision date: 10.05.2021

Page 11 of 14

1471316-72-9	Benzenesulfonic acids, di-C10-14-alkyl derivatives, calcium salts					
	Acute fish toxicity	LC50 mg/l	> 100	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50 mg/l	> 1000	72 h	Pseudokirchneriella subcapitata	Study report (1994) EPA OTS 797.1050
	Acute crustacea toxicity	EC50 mg/l	> 1000	48 h	Daphnia magna	Study report (1993) EPA OTS 797.1300
	Acute bacteria toxicity	(> 10000 mg/l)		3 h	activated sludge of a predominantly domestic sewage	Study report (1994) OECD Guideline 209

#### **12.2. Persistence and degradability**

There are no data available on the mixture itself. AOX (mg/l): 0

#### **12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

#### **Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
75-28-5	isobutane	1,09
74-98-6	propane	1,09
106-97-8	butane	1,09
1471316-72-9	Benzenesulfonic acids, di-C10-14-alkyl derivatives, calcium salts	> 6,91

#### **BCF**

CAS No	Chemical name	BCF	Species	Source
1174921-73-3	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	144,3	calculated	Other company data (
1471316-72-9	Benzenesulfonic acids, di-C10-14-alkyl derivatives, calcium salts	70,8	Fish, not further specified.	Study report (2013)

#### **12.4. Mobility in soil**

No information available.

#### **12.5. Results of PBT and vPvB assessment**

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

#### **12.7. Other adverse effects**

No information available.

### **SECTION 13: Disposal considerations**

#### **13.1. Waste treatment methods**

##### **Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

##### **List of Wastes Code - residues/unused products**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

##### **List of Wastes Code - used product**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

##### **List of Wastes Code - contaminated packaging**

**Safety Data Sheet**

according to UK REACH Regulation

Revision date: 10.05.2021

**Multi Signum Spray**

Page 12 of 14

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

**SECTION 14: Transport information****Land transport (ADR/RID)**

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
Hazard label: 2.1  
Classification code: 5F  
Special Provisions: 190 327 344 625  
Limited quantity: 1 L  
Excepted quantity: E0  
Transport category: 2  
Tunnel restriction code: D

**Inland waterways transport (ADN)**

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
Hazard label: 2.1  
Classification code: 5F  
Special Provisions: 190 327 344 625  
Limited quantity: 1 L  
Excepted quantity: E0

**Marine transport (IMDG)**

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
Hazard label: 2.1  
Marine pollutant: no  
Special Provisions: 63, 190, 277, 327, 344, 381,959  
Limited quantity: 1000 mL  
Excepted quantity: E0  
EmS: F-D, S-U

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS, flammable  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
Hazard label: 2.1  
Special Provisions: A145 A167 A802  
Limited quantity Passenger: 30 kg G  
Passenger LQ: Y203  
Excepted quantity: E0  
IATA-packing instructions - Passenger: 203

## Safety Data Sheet

according to UK REACH Regulation

# Multi Signum Spray

Revision date: 10.05.2021

Page 13 of 14

IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28

2010/75/EU (VOC): No information available.

2004/42/EC (VOC): No information available.

#### Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Aerosol directive (75/324/EEC)

#### National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

## SECTION 16: Other information

#### Changes

This data sheet contains changes from the previous version in section(s): 2,3,9,11.

#### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL (UK): Workplace Exposure Limits

TWA (EC): Time-Weighted Average

ATE: Acute Toxicity Estimate

STEL (EC) Short Term Exposure Limit

LC50: Lethal Concentration

EC50: half maximal Effective Concentration

ErC50: means EC50 in terms of reduction of growth rate

#### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
STOT SE 3; H336	Bridging principle "Aerosols"

#### Relevant H and EUH statements (number and full text)

H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

## Safety Data Sheet

according to UK REACH Regulation

### Multi Signum Spray

Revision date: 10.05.2021

Page 14 of 14

H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

#### Further Information

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]:  
Calculation method.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*